



Tipo UCFL 200

Tipo n.	Ø albero mm	Dimensioni (mm)										Bullone fissaggio mm	Cuscinetto n.	Supporto n.	Peso kg	Carico cuscinetto kg		
		a	e	i	g	l	s	b	Z	Bi	n					dinam.	statico	
UCFL 201	12													UC 201		0,5	1310	680
UCFL 202	15													UC 202		0,48	1310	680
UCFL 203	17	113	90	15	12	25,5	12	60	33,3	31	12,7	M 10		UC 203	FL 204	0,47	1310	680
UCFL 204	20													UC 204		0,45	1310	680
UCFL 205	25	130	99	16	14	27	16	68	35,7	34	14,3	M 14		UC 205	FL 205	0,63	1430	800
UCFL 206	30	148	117	18	14	31	16	80	40,2	38,1	15,9	M 14		UC 206	FL 206	0,96	2000	1150
UCFL 207	35	161	130	19	16	34	16	90	44,4	42,9	17,5	M 14		UC 207	FL 207	1,23	2640	1570
UCFL 208	40	175	144	21	16	36	16	100	51,2	49,2	19	M 14		UC 208	FL 208	1,58	2990	1830
UCFL 209	45	188	148	22	18	38	19	108	52,2	49,2	19	M 16		UC 209	FL 209	1,91	3350	2090
UCFL 210	50	197	157	22	18	40	19	115	54,6	51,6	19	M 16		UC 210	FL 210	2,19	3600	2370
UCFL 211	55	224	184	25	20	43	19	130	58,4	55,6	22,2	M 16		UC 211	FL 211	3,15	4400	3000
UCFL 212	60	250	202	29	20	48	23	140	68,7	65,1	25,4	M 20		UC 212	FL 212	4,08	5350	3700
UCFL 213	65	258	210	30	24	50	23	155	69,7	65,1	25,4	M 20		UC 213	FL 213	5,06	5850	4100
UCFL 214	70	265	216	31	24	54	23	160	75,4	74,6	30,2	M 20		UC 214	FL 214	6,01	6350	4500
UCFL 215	75	275	225	34	24	56	23	165	78,5	77,8	33,3	M 20		UC 215	FL 215	6,48	6750	4900
UCFL 216	80	290	233	34	24	58	25	180	83,3	82,6	33,3	M 22		UC 216	FL 216	8,02	7400	5400
UCFL 217	85	305	248	36	26	63	25	190	87,6	85,7	34,1	M 22		UC 217	FL 217	9,48	8500	6300
UCFL 218	90	320	265	40	26	68	25	205	96,3	96	39,7	M 22		UC 218	FL 218	11,88	9750	7300